

LALVIN BM4X4[™]

Saccharomyces cerevisiae

Increased aromatic intensity, color intensity, good length of finish and reliable fermentation performance

DESCRIPTION °

LALVIN BM4X4[™] is the result of an extensive study done in collaboration with INRAe (Montpellier, France) to optimize the performance of the popular yeast, LALVIN BM45[™]. The original yeast, LALVIN BM45[™], was selected by the Consorizo del Vino Brunello di Montalcino and the University of Sienna (Tuscany, Italy) for wines going through long macerations. The «Dynamic Synergy» process of optimizing positive interactions between yeast was successfully applied on LALVIN BM45[™], resulting on a more efficient and secure yeast called LALVIN BM4X4[™]. This product retains the same contribution of the original yeast with increased fermentation reliability.




LALLEMAND

LALLEMAND OENOLOGY

BENEFITS & RESULTS

During alcoholic fermentation, LALVIN BM4x4[™] releases a significant quantity of polysaccharides. This results in a round mouthfeel, increases color stability and lowers the astringency of tannins (by stabilizing and binding polyphenols in the must).


LALVIN BM4X4[™] is suited for red wines, where mouthfeel, color and reliable fermentation kinetics are sought. It is also suited to the production of full-bodied white wines





YSEO[™] signifies Yeast Security and Sensory Optimization, a unique Lallemand yeast production process to help overcome demanding fermentation conditions.

YSEO[™] improves the reliability of alcoholic fermentation by improving yeast quality and performance and reduces the risk of sensory deviation even under difficult conditions. YSEO[™] yeasts are 100% natural and non-GMO.



PROPERTIES* •

- Saccharomyces cerevisiae var. cerevisiae **Optimum fermentation temperature** range: 16 to 28 °C
- Alcohol tolerance up to 16% v/v
- Moderate lag phase
- Moderate fermentation rate
- Competitive ("Killer K2") factor active
- Not considered as MLF friendly. Ensure adequate adequate MLF management and nutrition program
- Low SO₂ production
- Low foam formation

*subject to fermentation conditions

INSTRUCTIONS FOR OENOLOGICAL USE

A. Rehydration without yeast protector

Dosage rate: 20 to 40 g/hL

- 1. Rehydrate the yeast in 10 times its weight in water (temperature between 35 °C and 40 °C).
- 2. Resuspend the yeast by gently stirring and wait for 20 minutes.
- 3. Mix the rehydrated yeast with a little juice/must, gradually adjusting the yeast suspension temperature to within 5-10 °C of the juice/must temperature.
- 4. Inoculate into the must.

B. Rehydration with a yeast protector

In musts with high alcohol potential (> 13% v/v), with low turbidity (< 80 NTU) or other challenging conditions, the use of one of our GO-FERM[™] products (wine yeast protector) during yeast rehydration is recommended. Follow rehydration instructions according to the selected GO-FERM[™] product.

Ontes:

The total rehydration time should not exceed 45 minutes. It is crucial that a clean container is used to rehydrate the yeast. Rehydration directly in must is generally not advisable. Ensure yeast nutrition is appropriately managed during fermentation.

PACKAGING AND STORAGE

- Available in 500 g and 10 kg
- Store in a cool dry place
- To be used once opened

	Distin	outed by:		

The information in this document is correct to the best of our knowledge. However, this data sheet should not be cons to be an express guarantee, nor does it have implications as to the sales condition of this product. November 2024.





Visionary biological solutions - Being original is key to your success. At Lallemand Oenology, we apply our passion for innovation, maximize our skill in production and share our expertise, to select and develop natural microbiological solutions. Dedicated to the individuality of your wine, we support your originality, we cultivate our own.

www.lallemandwine.com